

**LS4 MOTORS SPECIFICATION PARAMETERS:**

**PERFORMANCE**

Maximum Allowable Velocity:	50 (mm/sec)
Dynamic Stall Force:	4 (N)
Static Holding Force	4 (N) (reference value)
Non-Energized Stiffness	2.3 (N/μ)
Nominal Preload on Stage	36 (N)
Kf	1.6 to 2.4 (N/Volt command) – driver & Command dependant
Kfv	30 to 40 (N • sec/m)
Offset	0.8 to 2 (V) – Driver dependant
Attainable Resolution	Better than 20 nm – see application notes
Nominal Lifetime	20,000 hours under nominal operating conditions

**ELECTRICAL**

Maximal Voltage:	125 Vrms, 39.6KHz, sine wave
Maximal Current consumption:	130 mA rms
Maximal Power Consumption:	3.0 W

**ENVIRONMENTAL**

Ambient Temperature:	0 – 50 ° C
Storage:	-40 ° C - +70 ° C
Humidity:	0 – 80% non condensing

**MOTOR + CONDITIONING DEVICE**

Length:	42 mm
Width:	60 mm
Height:	19 mm
Weight:	80 gr

**MAINTENANCE:**

Once a year wipe ceramic strip with IPA without Detaching motor.  
Change conditioning device every 1 year typical.

For Further Information Contact ....	
Heason Technologies Group Ltd Tel: +44(0)1403 755800 Fax: +44(0)1403 755810 Email: sales@heason.com	
Freephone 0800 374903 <a href="http://www.heason.com">www.heason.com</a>	