


OFL-3232™ Open Frame Table



Product Dimensions

Dimensions - Top View



For Further Information Contact

Heason Technologies Group Ltd

Tel: +44(0)1403 755800

Fax: +44(0)1403 755810


Email: sales@heason.com

Freephone 0800 374903 www.heason.com

Heason
Technologies Group


OFL-3232™ Open Frame Table

Dimensions - Side View




OFL-3232™ Open Frame Table

Dimensions - Bottom View




OFL-3232™ Open Frame Table

Dimensions - Moving Envelope



Dimensions - Perspective



Travel (T)	Length (L)	A	B	C	D
25.00	32.00	28.000	30.000	25.000	26.750

OFL-3232™ Open Frame Table

Specifications

Travel (inches)	25 x 25	
Leadscrew Accuracy (per axis) (µm)	250	
Bidirectional Repeatability (µm)	6	
Flatness & Straightness (per axis)(µm)	135	
Orthogonality (arc-seconds)	50	
Load Capacity (kg) ¹	80	
Maximum Leadscrew Speed (rps)	15	
Moving Mass (kg)	Upper Axis Lower Axis	10.9 37.6
Total Mass (kg)	57.2	

Configurations²

Leadscrew	Lead (inch)	Precision	0.50, 0.40, 0.20, 0.10
	Lead (mm)	Precision	2
Motor	Stepper (oz-in)	400 step/rev 200 step/rev	118, others available 100, others available
	Servo		brush, brushless

Options

Encoder	Rotary (counts/rev.)	2000, 4000
	Linear (µm/count)	5, 1, 0.5, 0.1

¹ Please contact our Applications Engineers for loads exceeding 25kg.

² Standard configuration is highlighted.